

COMPUTER NETWORKS EX-1 - ADDITIONAL

The entire process can be broken down into following steps:

TCP Server –

1. using `create()`, Create TCP socket.
2. using `bind()`, Bind the socket to server address.
3. using `listen()`, put the server socket in a passive mode, where it waits for the client to approach the server to make a connection
4. using `accept()`, At this point, connection is established between client and server, and they are ready to transfer data.
5. Go back to Step 3.

TCP Client –

1. Create TCP socket.
2. connect newly created client socket to server.

TCP Server:

```
#include <stdio.h>
#include <netdb.h>
#include <netinet/in.h>
#include <stdlib.h>
#include <string.h>
#include <sys/socket.h>
#include <sys/types.h>
#define MAX 80
#define PORT 8080
#define SA struct sockaddr

// Function designed for chat between client and server.
void func(int connfd)
{
    char buff[MAX];
    int n;
    // infinite loop for ch
    for (;;) {
        bzero(buff, MAX);

        // read the message from client and copy it in buffer
        read(connfd, buff, sizeof(buff));
        // print buffer which contains the client contents
        printf("From client: %s\n To client : ", buff);
        bzero(buff, MAX);
        n = 0;
        // copy server message in the buffer
        while ((buff[n++] = getchar()) != '\n')
            ;
        // and send that buffer to client
```

```

        write(connfd, buff, sizeof(buff));

        // if msg contains "Exit" then server exit and chat ended.
        if (strncmp("exit", buff, 4) == 0) {
            printf("Server Exit...\n");
            break;
        }
    }

// Driver function
int main()
{
    int sockfd, connfd, len;
    struct sockaddr_in servaddr, cli;

    // socket create and verification
    sockfd = socket(AF_INET, SOCK_STREAM, 0);
    if (sockfd == -1) {
        printf("socket creation failed...\n");
        exit(0);
    }
    else
        printf("Socket successfully created..\n");
    bzero(&servaddr, sizeof(servaddr));

    // assign IP, PORT
    servaddr.sin_family = AF_INET;
    servaddr.sin_addr.s_addr = htonl(INADDR_ANY);
    servaddr.sin_port = htons(PORT);

    // Binding newly created socket to given IP and verification
    if ((bind(sockfd, (SA*)&servaddr, sizeof(servaddr))) != 0) {
        printf("socket bind failed...\n");
        exit(0);
    }
    else
        printf("Socket successfully binded..\n");

    // Now server is ready to listen and verification
    if ((listen(sockfd, 5)) != 0) {
        printf("Listen failed...\n");
        exit(0);
    }
    else
        printf("Server listening..\n");
    len = sizeof(cli);

    // Accept the data packet from client and verification
    connfd = accept(sockfd, (SA*)&cli, &len);
    if (connfd < 0) {
        printf("server accept failed...\n");

```

```

        exit(0);
    }
else
    printf("server accept the client...\n");

// Function for chatting between client and server
func(connfd);

// After chatting close the socket
close(sockfd);
}

```

TCP Client:

```

#include <netdb.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <sys/socket.h>
#define MAX 80
#define PORT 8080
#define SA struct sockaddr
void func(int sockfd)
{
    char buff[MAX];
    int n;
    for (;;) {
        bzero(buff, sizeof(buff));
        printf("Enter the string : ");
        n = 0;
        while ((buff[n++] = getchar()) != '\n')
            ;
        write(sockfd, buff, sizeof(buff));
        bzero(buff, sizeof(buff));
        read(sockfd, buff, sizeof(buff));
        printf("From Server : %s", buff);
        if ((strncmp(buff, "exit", 4)) == 0) {
            printf("Client Exit...\n");
            break;
        }
    }
}

int main()
{
    int sockfd, connfd;
    struct sockaddr_in servaddr, cli;
    // socket create and verification

```

```
sockfd = socket(AF_INET, SOCK_STREAM, 0);
if (sockfd == -1) {
    printf("socket creation failed...\n");
    exit(0);
}
else
    printf("Socket successfully created..\n");
bzero(&servaddr, sizeof(servaddr));

// assign IP, PORT
servaddr.sin_family = AF_INET;
servaddr.sin_addr.s_addr = inet_addr("127.0.0.1");
servaddr.sin_port = htons(PORT);

// connect the client socket to server socket
if (connect(sockfd, (SA*)&servaddr, sizeof(servaddr)) != 0) {
    printf("connection with the server failed...\n");
    exit(0);
}
else
    printf("connected to the server..\n");

// function for chat
func(sockfd);

// close the socket
close(sockfd);
}
```